



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 16000 miles / 12 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Drain fuel filter water trap.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check torque of towbar fixings (where fitted).	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 32000 miles / 24 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Renew fuel filter element.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check operation of door locks, hinges, door checks, bonnet catch and fuel flap (do not lubricate).	
Check torque of towbar fixings (where fitted).	
Check anti-freeze specific gravity.	
Replace the air cleaner element.	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Check for free play in all suspension and body mounting rubbers.	
Check ball joints anchors, steering system tie rods, and also the condition of the ball joints and protective boots.	
Check visually brake servo hose, brake, fuel and PAS pipes, unions and electrical harnesses for chafing, leaks and corrosion.	
Check for fluid leaks.	
Check exhaust system for leaks, security and damage.	
Check steering rod ball joint fixings and condition of ball joints, dust covers and EPAS water drain valve.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 48000 miles / 36 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Drain fuel filter water trap.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check torque of towbar fixings (where fitted).	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

Replace brake fluid.*	
If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*	

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 64000 miles / 48 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Renew fuel filter element.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check operation of door locks, hinges, door checks, bonnet catch and fuel flap (do not lubricate).	
Check torque of towbar fixings (where fitted).	
Check anti-freeze specific gravity.	
Replace the air cleaner element.	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Check for free play in all suspension and body mounting rubbers.	
Check ball joints anchors, steering system tie rods, and also the condition of the ball joints and protective boots.	
Check visually brake servo hose, brake, fuel and PAS pipes, unions and electrical harnesses for chafing, leaks and corrosion.	
Check for fluid leaks.	
Check exhaust system for leaks, security and damage.	
Check steering rod ball joint fixings and condition of ball joints, dust covers and EPAS water drain valve.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 80000 miles / 60 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Drain fuel filter water trap.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check torque of towbar fixings (where fitted).	
Renew Dynamic Response fluid reservoir (where fitted).	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Renew transfer box oil.	
Renew locking differential oil.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 96000 miles / 72 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Renew fuel filter element.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check operation of door locks, hinges, door checks, bonnet catch and fuel flap (do not lubricate).	
Check torque of towbar fixings (where fitted).	
Check anti-freeze specific gravity.	
Replace the air cleaner element.	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Check for free play in all suspension and body mounting rubbers.	
Check ball joints anchors, steering system tie rods, and also the condition of the ball joints and protective boots.	
Check visually brake servo hose, brake, fuel and PAS pipes, unions and electrical harnesses for chafing, leaks and corrosion.	
Check for fluid leaks.	
Check exhaust system for leaks, security and damage.	
Check steering rod ball joint fixings and condition of ball joints, dust covers and EPAS water drain valve.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

Replace brake fluid.*	
Replace all flexible brake hoses.*	
If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*	

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 112000 miles / 84 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Drain fuel filter water trap.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check torque of towbar fixings (where fitted).	
Check condition of ancillary drive belt.	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 128000 miles / 96 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Renew fuel filter element.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check operation of door locks, hinges, door checks, bonnet catch and fuel flap (do not lubricate).	
Check torque of towbar fixings (where fitted).	
Check anti-freeze specific gravity.	
Replace the air cleaner element.	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Check for free play in all suspension and body mounting rubbers.	
Check ball joints anchors, steering system tie rods, and also the condition of the ball joints and protective boots.	
Check visually brake servo hose, brake, fuel and PAS pipes, unions and electrical harnesses for chafing, leaks and corrosion.	
Check for fluid leaks.	
Check exhaust system for leaks, security and damage.	
Check steering rod ball joint fixings and condition of ball joints, dust covers and EPAS water drain valve.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 144000 miles / 108 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Drain fuel filter water trap.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check torque of towbar fixings (where fitted).	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	
Report any unusual features of vehicle condition and additional work required.	

OPTIONAL SERVICE ITEMS

Replace brake fluid.*	
If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*	

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					



ABOVE & BEYOND

Service schedule

Customer copy

SERVICE TYPE: 160000 miles / 120 months service
MODEL: Range Rover / L405

V.I.N.: [REDACTED]

Please note that service intervals always represent the maximum time and distance that should exist between servicing. Driving style and conditions may necessitate earlier servicing as indicated by the notifications on your instrument panel.

SERVICE ITEMS

Check condition and security of seats and seat belts.	
Check operation of all lamps, horns and warning indicators.	
Check operation of Windshield and headlight wipers and washer jets.	
Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re-select HIGH range gears.	
Renew pollen filter.	
Check tire pressures, condition, tread depth, signs of uneven wear and suitability (including spare).	
Remove road wheels.	
Inspect brake pads for wear, calipers for leaks and disks for condition.	
Renew fuel filter element.	
Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore).	
Check operation of door locks, hinges, door checks, bonnet catch and fuel flap (do not lubricate).	
Check torque of towbar fixings (where fitted).	
Check anti-freeze specific gravity.	
Replace the air cleaner element.	
Renew ancillary driving belts.	
Renew Dynamic Response fluid reservoir (where fitted).	
Check/top-up brake and Dynamic Response fluid levels and screen washer reservoirs.	
Renew engine oil and filter.	
Check for debris from auxiliary oil cooler and radiator.	
Renew transfer box oil.	
Renew locking differential oil.	
Renew front and rear non-locking differential oil.	
Renew the automatic transmission oil and filter.	
Check for free play in all suspension and body mounting rubbers.	
Check ball joints anchors, steering system tie rods, and also the condition of the ball joints and protective boots.	
Check visually brake servo hose, brake, fuel and PAS pipes, unions and electrical harnesses for chafing, leaks and corrosion.	
Check for fluid leaks.	
Check exhaust system for leaks, security and damage.	
Check steering rod ball joint fixings and condition of ball joints, dust covers and EPAS water drain valve.	
Carry out road test.	
Reset service indicator.	
Reset engine oil level indicator.	
Endorse service record.	

OPTIONAL SERVICE ITEMS

Renew engine coolant.*	
If fault lamp(s) are illuminated, interrogate that system using the JLR approved diagnostic equipment and report findings.*	

	L/F	R/F	L/R	R/R	SPARE
Tyre Pressure					
Tyre Tread Depth					
Tyre Condition					