

## THE ALL-NEW RANGE ROVER SPORT TECHNICAL DATA

	3.0L V6 Diesel 258PS	3.0L V6 Diesel 292PS	4.4L V8 Diesel	3.0L V6 Supercharged Petrol	5.0L V8 Supercharged Petrol
Height mm (in)	1780 / 70.1				
Width excl. wing mirrors / wing mirrors folded mm (in)	1983 (78.1) / 2073 (81.6)				
Length mm (in)	4850 (191)				
Wheelbase mm (in)	2923 (115.1)				
Approach angle deg	33.0 (off-road height)				
Departure angle deg	31.0 (off-road height)				
Ramp breakover angle deg	27.0 (off-road height)				
Wading depth mm (in)	850 (33.5)				
Turning circle m (ft)	12.6 (41.3)				
Drag coefficient (Cd)	0.34	0.34	0.36	0.37	0.37
Weight from kg	2115	2115	2398	2144	2310
Front suspension	SLA suspension with twin lower links with air springs/ CVD with Passive ARB	SLA suspension with twin lower links with air springs/CVD with Passive ARB or optional ARC	SLA suspension with twin lower links with air springs/CVD with Passive ARB or optional ARC	SLA suspension with twin lower links with air springs/CVD with Passive ARB or optional ARC	SLA suspension with twin lower links with air springs/CVD with ARC
Rear suspension	Integral link suspension with air springs/ CVD with Passive ARB	Integral link suspension with air springs/ CVD with Passive ARB or optional ARC	Integral link suspension with air springs/ CVD with Passive ARB or optional ARC	Integral link suspension with air springs/ CVD with Passive ARB or optional ARC	Integral link suspension with air springs/ CVD with ARC
Brakes	350mm ventilated disc front / 350mm ventilated disc rear	380mm ventilated disc front / 365mm ventilated disc rear	380mm ventilated disc front / 365mm ventilated disc rear	350mm ventilated disc front / 350mm ventilated disc rear	380mm ventilated disc front / 365mm ventilated disc rear
Steering	Electric Power Assisted Steering (EPAS) rack and pinion				
Four wheel drive system	Permanent four-wheel drive with standard locking centre differential & Terrain Response™ 2, optional locking rear axle differential.				
Engine type	Longitudinal / V6 / 24 valves	Longitudinal / V6 / 24 valves	Longitudinal / V8 / 32	Longitudinal / V6 / 24 Quad cam DIVCT (Dual Independent Variable Cam Timing)	Longitudinal / V8 / 32 Quad cam DIVCT (Dual Independent Variable Cam Timing)
Displacement cc (cu.in)	2993 (182.6)	2993 (182.6)	4367 (266.5)	2995 (182.8)	4999.7 (305.1)
Bore / Stroke mm (in)	84.0 / 90.0 (3.31 / 3.54)	84.0 / 90.0 (3.31 / 3.54)	84.0 / 98.5 (3.30 / 3.88)	84.5 / 89.0 (3.33 / 3.50)	92.5 / 93.0 (3.64 / 3.66)
Compression ratio: 1	16.1	16.1	16.1	10.5	9.5
Max Power PS (kW)	258 (190)	292 (215)	339 (250)	340 (250)	510 (375)
Max Power US bhp	N/A	N/A	N/A	340	510
Max Torque Nm (lb ft)	600 (N/A)	600 (N/A)	700 (N/A)	450 (332)	625 (461)
Transmission	ZF 8HP70	ZF 8HP70	ZF 8HP70	ZF 8HP70	ZF 8HP70
Emissions	EU5	EU5	EU5	EU5	EU5
CO <sub>2</sub> EU Combined	194	199	229	249	298
Fuel tank capacity litres	77	77	105	105	105
0-60 mph	7.1	6.8	6.5	6.9	5.0
0-100 km/h	7.6	7.2	6.9	7.2	5.3
Top speed mph	130	130 (138 opt)	140	130	140 (155 opt)