# REAR DRIVE AXLE/DIFFERENTIAL (G1754035)

SPECIFICATIONS

#### Sealers

ITEM	LAND ROVER PART NO.
Input shaft splines	STC 50554
Differential casing	STC 50550

#### Lubricants

ITEM	SPECIFICATION	
* Recommended lubricant:		
Open unit - all variants except Hybrid Electric Vehicles(HEV)	Castrol SAF-XO - 75W/90	
Open unit - Hybrid Electric Vehicles(HEV)	Castrol BOT 750b	
ETM unit	Castrol BOT 720	

### \* Do not use any lubricant other than that specified

#### Capacities

UNIT	SERVICE FILL CAPACITY
Open differential	Wet: 0.82 liters (1.73 pints) (0.87 US quarts)
	Dry: 0.85 liters (1.79 pints) (0.89 US quarts)
ETM differential	Wet: 1.21 liters (2.56 pints) (1.28 US quarts)
	Dry: 1.25 liters (2.64 pints) (US quarts 1.32)

#### **Rear 'Open' Differential**

ITEM	SPECIFICATION	
Reduction ratio:		
Vehicles with 2.0L petrol engine	3.21:1	

ITEM	SPECIFICATION	
Vehicles with 3.0L supercharged petrol engine	3.73:1	
Vehicles with 5.0L supercharged petrol engine	3.31:1	
Vehicles with 3.0L diesel engine	3.21:1	
Vehicles with 4.4L diesel engine	2.73:1	

## **Torque Specifications**

DESCRIPTION	NM	LB-FT
* Oil drain plug	30	22
* Oil filler plug	30	22
Oil temperature sensor	22	16
++ Differential locking motor	10	7
Differential front mounting bolts	110	81
Differential rear mounting bolt	170	125
Rear damper bolt	80	59

## ++ Apply sealant, Part No. STC 50550 to flange of locking motor

\* A new plug must be installed

djhjaGVzaGlyZWtvdDsyMDlxLTA0LTlzVDE50jQ00jl4LjQ3N1o7MTQzLjI0NC40MC40NTtTQUxHQTJBSjJKQTM4NzAwNw==